


LED wall mounted fitting



GENERAL DATA:

Colour: white

Place of assembly: wall mounted

Place of application: Indoors

Minimum distance from the illuminated object: 0,2m

Compatible with a dimmer: no

On switch: yes

Length [mm]: 370

Width [mm]: 51

Height [mm]: 121

Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Maximum power [W]: 3,3

Class of protection against electric shock: II

Lampshade material: plastic

Diode type: LED SMD

Luminous flux [lm]: 145

Useful luminous flux of the light source Φ_{use} [lm]: 145

Useful luminous flux of the light source Φ_{use} [lm]: in narrow cone (90°)

Colour temperature: Warm white

Correlated colour temperature [K]: 3000

Colour consistency in McAdam ellipses: ≤ 6

Colour rendering index: 80

Service life [h]: 20000

Number of on/off cycles: ≥ 15000

Lighting angle [°]: 30

Luminous efficiency of the lamp [lm/W]: 44

Ambient temperature range to which the product can be exposed: 5÷25

Enclosure material: aluminum alloy

Connection type: Bolt terminal block

Range of sections of wires used [mm²]: 0,5-1,5

Lamp-heating time [s]: ≤ 1

Lamp-ignition time [s]: $\leq 0,5$

The fixture is movable horizontally [°]: 360

The fixture is movable vertically [°]: 360

IP class: 20

LED wall mounted fitting

