

Kanlux SMART

LED fényforrás



[V] 220-240 AC	[Hz] 50	ellipse ≤ 6x MacAdam	Ra 80	≥25000	15000 [h]	Hg
APP WiFi 2,4 GHz/BLE	CE	EAC	UK CA	↓		



S A60 7W E27 CCT



	PoN [W]	[W]	[lm] Φ _{Use}	T _c [K]	[°]	E	E	E
S A60 7W E27 CCT	33640	7	60	806	2700-6500	320	E27	E
S A60 9W E27 RGB CCT	33641	9	60	806	2700-6500	180	E27	F
S A60 11,5W E27 RGB CCT	33642	11,5	75	1055	2700-6500	180	E27	F
S GU10 4,7W RGB CCT	33643	4,7	39	325	2700-6500	110	GU10	G
S C37 4,9W E14 RGB CCT	33644	4,9	40	470	2700-6500	180	E14	F



Létrehozás dátuma: 30.01.2023, 13:04

Fenntartjuk a műszaki változtatások bevezetésének jogát. A jelen anyagban található adatok jogi szempontból nem kötelező érvényűek.

Kanlux SMART

LED fényforrás



S A60 7W E27 CCT



S A60 9W E27 RGBCCT




S A60 11,5WE27 RGBCCT




S GU10 4,7W RGBCCT




S C37 4,9W E14 RGBCCT




S A60 7W E27 CCT




S A60 9W E27 RGBCCT



S A60 11,5WE27 RGBCCT



S GU10 4,7W RGBCCT



S C37 4,9W E14 RGBCCT