

Kanlux SMART

LED източник на светлина



[V] 220-240 AC	[Hz] 50	ellipse ≤ 6x MacAdam	Ra 80	≥25000	15000 [h]	Hg
APP WiFi 2,4 GHz/BLE	CE	EAC	UK CA	↓		



S A60 7W E27 CCT



	Power (W)	Beam angle (lm)	Temperature (K)	Beam angle (°)	Base	Energy efficiency class (Ei)
S A60 7W E27 CCT	33640	7	60	806	2700-6500	320 E27 E
S A60 9W E27 RGBCCT	33641	9	60	806	2700-6500	180 E27 F
S A60 11,5W E27 RGBCCT	33642	11,5	75	1055	2700-6500	180 E27 F
S GU10 4,7W RGBCCT	33643	4,7	39	325	2700-6500	110 GU10 G
S C37 4,9W E14 RGBCCT	33644	4,9	40	470	2700-6500	180 E14 F



Kanlux SMART

LED източник на светлина



S A60 7W E27 CCT



S A60 9W E27 RGBCCT




S A60 11,5WE27 RGBCCT




S GU10 4,7W RGBCCT




S C37 4,9W E14 RGBCCT




S A60 7W E27 CCT




S A60 9W E27 RGBCCT



S A60 11,5WE27 RGBCCT



S GU10 4,7W RGBCCT



S C37 4,9W E14 RGBCCT