

HIERRO

линейно LED осветително тяло

DALI
system

low
UGR



HIGH
efficacy

5
WARRANTY
3 years

BRANDED
components








 [V] 220-240 AC	 [Hz] 50	 ≥ 30000	 [lm] 50000	 ellipse $\leq 6x$ Macldam	 Ra 80	 SMD
 DALI		 IP 20		 [°C] 5÷25		
 [mm ²] 0,5÷2,5		 0,5m				



HRD-ML-WW-W-NT

HIERRO

линейно LED осветително тяло

							
	[W]	Tc [K]	TYPE	[°]		[lm]	[mm]
HRD-ML-WW-W-NT	36988	18	3000	растер	X60/Y60	бял	2350 570
HRD-MM-WW-W-NT	36989	23	3000	растер	X60/Y60	бял	2850 570
HRD-MH-WW-W-NT	36990	28	3000	растер	X60/Y60	бял	3300 570
HRD-ML-WW-B-NT	36994	18	3000	растер	X60/Y60	черен	2100 570
HRD-MM-WW-B-NT	36995	23	3000	растер	X60/Y60	черен	2500 570
HRD-MH-WW-B-NT	36996	28	3000	растер	X60/Y60	черен	2900 570
HRD-ML-WN-W-NT	37000	18	3500	растер	X60/Y60	бял	2400 570
HRD-MM-WN-W-NT	37001	23	3500	растер	X60/Y60	бял	2900 570
HRD-MH-WN-W-NT	37002	28	3500	растер	X60/Y60	бял	3350 570
HRD-ML-WN-B-NT	37006	18	3500	растер	X60/Y60	черен	2150 570
HRD-MM-WN-B-NT	37007	23	3500	растер	X60/Y60	черен	2600 570
HRD-MH-WN-B-NT	37008	28	3500	растер	X60/Y60	черен	3000 570
HRD-ML-NW-W-NT	37012	18	4000	растер	X60/Y60	бял	2450 570
HRD-MM-NW-W-NT	37013	23	4000	растер	X60/Y60	бял	3000 570
HRD-MH-NW-W-NT	37014	28	4000	растер	X60/Y60	бял	3450 570
HRD-ML-NW-B-NT	37018	18	4000	растер	X60/Y60	черен	2200 570
HRD-MM-NW-B-NT	37019	23	4000	растер	X60/Y60	черен	2650 570
HRD-MH-NW-B-NT	37020	28	4000	растер	X60/Y60	черен	3050 570

- Материал на корпуса: стомана, пластмаса
- Материал на дифузера: пластмаса



HIERRO

линейно LED осветително тяло



HRD-ML-WW-W-NT



HRD-MM-WW-W-NT



HRD-MH-WW-W-NT



HRD-ML-WW-B-NT



HRD-MM-WW-B-NT



HRD-MH-WW-B-NT



HRD-ML-WN-W-NT



HRD-MM-WN-W-NT



HRD-MH-WN-W-NT



HRD-ML-WN-B-NT



HRD-MM-WN-B-NT



HRD-MH-WN-B-NT



HRD-ML-NW-W-NT



HRD-MM-NW-W-NT



HRD-MH-NW-W-NT



HRD-ML-NW-B-NT

HIERRO


линейно LED осветително тяло



HRD-MM-NW-B-NT



HRD-MH-NW-B-NT



HRD-MH-NT

