

iQ-LED

Kanlux

IQ-LED C37

Světelný zdroj LED



[V] 220-240 AC	[Hz] 50	SMD	360° Φ _{use}	ellipse ≤ 6x MacAdam	Ra 80	≥40000
(h) 25000	Hg		CE	EAC	UK CA	



IQ-LED C37E14 4,2W-WW



		Pon [W]	[W]	[lm] Φ _{use}	T _c [K]	[°]	E14	Ei
IQ-LED C37E14 4,2W-WW	33728	4,2	40	470	2700	300	E14	E
IQ-LED C37E14 4,2W-NW	33729	4,2	40	470	4000	300	E14	E
IQ-LED C37E14 7,2W-WW	33731	7,2	60	806	2700	280	E14	E
IQ-LED C37E14 7,2W-NW	33732	7,2	62	840	4000	280	E14	E
IQ-LED C37E14 7,2W-CW	33733	7,2	62	840	6500	280	E14	E

Kanlux IQ-LED znamená fotobiologickou bezpečnost, šetrnou teplotu barev očím a spolehlivost, to vše v klasickém designu C37. Žárovky Kanlux IQ-LED poskytují plný komfort používání a bezpečnost.

iQ^{LED}

Kanlux

IQ-LED C37

Světelný zdroj LED



IQ-LED C37E14 4,2W-WW



IQ-LED C37E14 4,2W-NW



IQ-LED C37E14 7,2W-WW



IQ-LED C37E14 7,2W-NW




IQ-LED C37E14 7,2W

iQ LED


Kanlux

IQ-LED C37

Světelný zdroj LED



IQ-LED C37E14 4,2W



IQ-LED C37E14 7,2W