

FIZU


Downlight



[V] 220-240 AC	[Hz] 50	[W] 4,8	[h] ≥15000	[h] 25000	ellipse ≤ 6x Mackdam	Ra 80
SMD				5÷25		
[mm²] 0,5-2,5	[mm] Ø65	0,5m	90° Φ _{use}			



FIZU IP44 4,8W NW-W



Model	Part No.	[W]	Tc [K]	[lm]	Φ _{use}	Beam Angle	Beam Diameter	Beam Length	Beam Diameter	Color	Beam Type
FIZU IP44 4,8W NW-W	38260	4,8	4000	420	36					weiß	F
FIZU IP44 4,8W NW-B	38261	4,8	4000	420	36					schwarz	F
FIZU 4,8W NW-W	38262	4,8	4000	420	36	30	in einer Achse			weiß	F
FIZU 4,8W NW-B	38263	4,8	4000	420	36	30	in einer Achse			schwarz	F
FIZU 4,8W WW-W	38264	4,8	3000	420	36	30	in einer Achse			weiß	F
FIZU 4,8W WW-B	38265	4,8	3000	420	36	30	in einer Achse			schwarz	F

- Gehäusematerial: Kunststoff
- Abdeckungsmaterial: Kunststoff



FIZU

Downlight



FIZU IP44 4,8W NW-W



FIZU IP44 4,8W NW-B



FIZU 4,8W NW-W




FIZU 4,8W NW-B




FIZU 4,8W WW-W




FIZU 4,8W WW-B




FIZU IP44 4,8W NW-W




FIZU IP44 4,8W NW-B




FIZU 4,8W NW-W



FIZU 4,8W NW-B



FIZU 4,8W WW-W



FIZU 4,8W WW-B