

KDB-series distribution board





KDB-S06T

			In [A]			IP
KDB-S06T	23610	white / blue	63	6P	wall mounted	30
KDB-S08T	23611	white / blue	63	8P	wall mounted	30
KDB-S12T	23612	white / blue	63	12P	wall mounted	30
KDB-S18T	23613	white / blue	63	18P	wall mounted	30
KDB-S24T	23614	white / blue	63	2x12P	wall mounted	30
KDB-S36T	23615	white / blue	63	2x18P	wall mounted	30
KDB-F06T	23616	white / blue	63	6P	Recessed mount in the wall	30
KDB-F08T	23617	white / blue	63	8P	Recessed mount in the wall	30
KDB-F12T	23618	white / blue	63	12P	Recessed mount in the wall	30
KDB-F18T	23619	white / blue	63	18P	Recessed mount in the wall	30
KDB-F24T	23620	white / blue	63	2x12P	Recessed mount in the wall	30
KDB-F36T	23621	white / blue	63	2x18P	Recessed mount in the wall	30
KDB-F12P	23622	white	63	12P	Recessed mount in the wall	30
KDB-F24P	23623	white	63	2x12P	Recessed mount in the wall	30
KDB-S12P	23624	white	63	1x12P	wall mounted	30
KDB-S24P	23625	white	63	2x12P	wall mounted	30
KDB-F36P	23628	white	63	2x18P	Recessed mount in the wall	30
KDB-S36P	23629	white	63	2x18P	wall mounted	30
KDB-S24PM	24178	white	63	-	wall mounted	30
KDB-F54P	28340	white	63	3x18P	Recessed mount in the wall	30
KDB-F54P-M	28341	white	63	18P	Recessed mount in the wall	30

Date of issue: 25.06.2024, 11:05

We reserve the right to make technical changes. The data contained in this material are not legally binding.



KDB-series distribution board

KDB series switchboards meeting the requirement for heat resistance at the temperature of 650°C, can be used on non-flammable surfaces only (e.g. full solid walls made of non-combustible materials). They cannot be used on flammable surfaces (e.g. plasterboard, wood boards, etc.), on the so-called "hollow walls" or on technical sections

· Material: plastic





KDB-series distribution board























KDB-F54P-M









KDB-S18T




KDB-series distribution board





KDB-series distribution board



KDB-F54P-M

