

FUTURIO LED DALI 28W 1180mm

LED dustproof lighting fitting



[V] 220-240 AC	[Hz] 50	 ≥30000	 50000	 ≤3x MacAdam	 80	 SMD
 DALI		IP 65			IK 08	
 0.5÷2.5	 0,5m	CE	EAC	PZH	UK CA	



FTD1200 28W-840-OPL

	[V]	Tc [K]	TYPE	[°]	[lm]	lm/W	[mm]	°C	
FTD1200 28W-840-OPL	28854	28	4000	opal	X130/Y110	4100	146	1180	-25÷40
FTD1200 28W-840-RYF	28855	28	4000	grooved	X115/Y105	4500	161	1180	-25÷40
FTD1200 28W-840-INT	28856	28	4000	prismatic, narrow-beam	X70/Y95	4300	154	1180	-25÷40
FTD1200 28W-840-ASY	28857	28	4000	prismatic, asymmetric	X75/Y95	4300	154	1180	-25÷40

- Enclosure material: PC
- Lamphshade material: PC



FTD1200 28W-840-OPL



FTD1200 28W-840-RYF




FTD1200 28W-840-INT




FTD1200 28W-840-ASY

FUTURIO LED DALI 28W 1180mm


LED dustproof lighting fitting




FTD1200 28W-840-OPL



FTD1200 28W-840-RYF



FTD1200 28W-840-INT



FTD1200 28W-840-ASY