

iQ-LED

Kanlux

IQ-LED GU10

LED light source



[V] 220-240 AC	[Hz] 50	PAR16	SMD	ellipse ≤ 6x MacAdam	Ra 95	≥40000
25000 [h]	Hg		CE	EAC	UK CA	



IQ-LED GU10 6,5W-WW



Model	Part No.	Power [W]	Beam Angle [°]	Light Output [lm]	Beam Diameter [mm]	Mounting Height [mm]	Beam Diameter [mm]	Base	Class
IQ-LED GU10 6.5W-WW	35240	6.5	59	580	510	2700	110	GU10	F
IQ-LED GU10 6.5W-NW	35241	6.5	60	585	515	4000	110	GU10	F
IQ-LED GU10 6.5W-CW	35242	6.5	60	585	515	6500	110	GU10	F
IQ-LED GU10 6.5WS3-WW	35243	6.5	85	580	535	2700	36	GU10	F
IQ-LED GU10 6.5WS3-NW	35244	6.5	86	580	540	4000	36	GU10	F
IQ-LED GU10 6.5WS3-CW	35245	6.5	86	580	540	6500	36	GU10	F
IQ-LED GU10 4.5W-WW	35249	4.5	39	410	350	2700	110	GU10	F
IQ-LED GU10 4.5W-NW	35250	4.5	40	420	355	4000	110	GU10	F
IQ-LED GU10 4.5W-CW	35251	4.5	40	420	355	6500	110	GU10	F

Kanlux IQ-LED means photo-biological safety, colour temperature friendly to eyes and reliability. Now, all this in a new version with GU10 light bulb base. IQ-LED bulbs ensure full comfort of use and safety.

- Lampshade material: plastic

Date of issue: 02.02.2024, 14:22

We reserve the right to make technical changes. The data contained in this material are not legally binding.

EN

iQ-LED

Kanlux

IQ-LED GU10

LED light source




IQ-LED GU10 6,5W




IQ-LED GU10 6,5WS3




IQ-LED GU10 4,5W



IQ-LED GU10 6,5W



IQ-LED GU10 6,5WS3



IQ-LED GU10 4,5W