

FUTURIO LED 49W 1180mm

Plafoniera stagna led



[V] 220-240 AC	[Hz] 50	≥30000	50000	ellipse ≤3x MacAdam	Ra 80	SMD
		IP 65			IK 08	
[mm ²] 1,5+2,5	0,5m					



FT1200 49W-840-OPL

	[W]	Tc [K]	TYPE	[°]	[lm]	lm/W	[mm]	[°C]	
FT1200 49W-840-OPL	28644	49	4000	opalescente	X130/Y110	6200	127	1180	-25÷35
FT1200 49W-840-RYF	28645	49	4000	grooved	X115/Y105	6700	137	1180	-25÷35
FT1200 49W-840-INT	28647	49	4000	prismatico, a fascio stretto	X70/Y95	6500	133	1180	-25÷35
FT1200 49W-840-ASY	28648	49	4000	prismatico, asimmetrico	X75/Y95	6500	133	1180	-25÷35

- 5 anni di garanzia secondo le condizioni della dichiarazione di garanzia consultabile sul sito Internet
- Materiale del corpo: PC
- Materiale del diffusore: PC



FT1200 49W-840-OPL



FT1200 49W-840-RYF




FT1200 49W-840-INT




FT1200 49W-840-ASY

FUTURIO LED 49W 1180mm


Plafoniera stagna led




FT1200 49W-840



FT1200 49W-840



FT1200 49W-840



FT1200 49W-840