

## HIERRO

### Plafoniera LED lineare



[V] 220-240 AC	[Hz] 50	≥30000	[h] 50000	ellipse ≤ 6x Macadam	Ra 80	SMD
		<b>IP</b> 20		[°C] 5÷25		
[mm²] 1,5÷2,5		0,5m				



#### HR-SL-WW-W-PT

	[W]	Tc [K]		[°]	[mm]	[m]	[mm]
HR-SL-WW-W-PT <b>37024</b>	9	3000	raster	X60/Y60	bianco	1150	315
HR-SH-WW-W-PT <b>37025</b>	14	3000	raster	X60/Y60	bianco	1650	315
HR-SL-WW-B-PT <b>37032</b>	9	3000	raster	X60/Y60	nero	1050	315
HR-SH-WW-B-PT <b>37033</b>	14	3000	raster	X60/Y60	nero	1450	315
HR-SL-WN-W-PT <b>37040</b>	9	3500	raster	X60/Y60	bianco	1200	315
HR-SH-WN-W-PT <b>37041</b>	14	3500	raster	X60/Y60	bianco	1700	315
HR-SL-WN-B-PT <b>37048</b>	9	3500	raster	X60/Y60	nero	1050	315
HR-SH-WN-B-PT <b>37049</b>	14	3500	raster	X60/Y60	nero	1500	315
HR-SL-NW-W-PT <b>37056</b>	9	4000	raster	X60/Y60	bianco	1250	315
HR-SH-NW-W-PT <b>37057</b>	14	4000	raster	X60/Y60	bianco	1700	315
HR-SL-NW-B-PT <b>37064</b>	9	4000	raster	X60/Y60	nero	1100	315
HR-SH-NW-B-PT <b>37065</b>	14	4000	raster	X60/Y60	nero	1550	315

- Materiale del corpo: metallo, plastica
- Diffusore: plastica

## HIERRO

Plafoniera LED lineare



HR-SL-WW-W-PT



HR-SH-WW-W-PT



HR-SL-WW-B-PT



HR-SH-WW-B-PT



HR-SL-WN-W-PT



HR-SH-WN-W-PT



HR-SL-WN-B-PT



HR-SH-WN-B-PT



HR-SL-NW-W-PT



HR-SH-NW-W-PT



HR-SL-NW-B-PT




HR-SH-NW-B-PT

## HIERRO

---

Plafoniera LED lineare



HR-S-PT

