

## FUTURIO LED DALI 28W 1180mm

Oprawa płytuszczelna LED



[V] 220-240 AC	[Hz] 50	≥30000	[h] 50000	ellipse ≤3x MacAdam	Ra 80	SMD
DALI		IP 65		IK 08		
[mm²] 0,5÷2,5	0,5m					



### FTD1200 28W-840-OPL

	[W]	Tc [K]				[°]	[lm]	lm/W	[mm]	[°C]
FTD1200 28W-840-OPL	<b>28854</b>	28	4000	opalowy	X130/Y110	4100	146	1180	-25÷40	
FTD1200 28W-840-RYF	<b>28855</b>	28	4000	ryflowany	X115/Y105	4500	161	1180	-25÷40	
FTD1200 28W-840-INT	<b>28856</b>	28	4000	pryzmatyczny, wąskostrumieniowy	X70/Y95	4300	154	1180	-25÷40	
FTD1200 28W-840-ASY	<b>28857</b>	28	4000	pryzmatyczny, asymetryczny	X75/Y95	4300	154	1180	-25÷40	

- 5 lat Gwarancji na warunkach oświadczenia gwarancyjnego, dostępnego na stronie internetowej
- Atest PZH: Numer BK/K/0163/01/2019, ważny do 2024-08-07
- Materiał obudowy: PC
- Materiał klosza: PC

## FUTURIO LED DALI 28W 1180mm

Oprawa pyłoszczelna LED



FTD1200 28W-840-OPL




FTD1200 28W-840-RYF




FTD1200 28W-840-INT




FTD1200 28W-840-ASY




FTD1200 28W-840-OPL



FTD1200 28W-840-RYF



FTD1200 28W-840-INT



FTD1200 28W-840-ASY