

Corp de iluminat liniar LED



[V] 220-240 AC	[Hz] 50	≥ 30000	[lm] 50000	ellipse $\leq 6x$ MacAdam	Ra 80	SMD
		IP 20		[°C] 5÷25		
[mm ²] 1,5÷2,5		0,5m				



HR-SL-WW-W-NT

	[W]	Tc [K]	TYPE	[°]		[mm]		
HR-SL-WW-W-NT	36940	9	3000 raster	X60/Y60	alb	1150	290	
HR-SH-WW-W-NT	36941	14	3000 raster	X60/Y60	alb	1650	290	
HR-SL-WW-B-NT	36948	9	3000 raster	X60/Y60	negru	1050	290	
HR-SH-WW-B-NT	36949	14	3000 raster	X60/Y60	negru	1450	290	
HR-SL-WN-W-NT	36956	9	3500 raster	X60/Y60	alb	1200	290	
HR-SH-WN-W-NT	36957	14	3500 raster	X60/Y60	alb	1700	290	
HR-SL-WN-B-NT	36964	9	3500 raster	X60/Y60	negru	1050	290	
HR-SH-WN-B-NT	36965	14	3500 raster	X60/Y60	negru	1500	290	
HR-SL-NW-W-NT	36972	9	4000 raster	X60/Y60	alb	1250	290	
HR-SH-NW-W-NT	36973	14	4000 raster	X60/Y60	alb	1700	290	
HR-SL-NW-B-NT	36980	9	4000 raster	X60/Y60	negru	1100	290	
HR-SH-NW-B-NT	36981	14	4000 raster	X60/Y60	negru	1550	290	

- Materialul carcasei: oțel, material din plastic
- Materialul abajurului: material din plastic

HIERRO

Corp de iluminat liniar LED



HR-SL-WW-W-NT



HR-SH-WW-W-NT



HR-SL-WW-B-NT



HR-SH-WW-B-NT



HR-SL-WN-W-NT



HR-SH-WN-W-NT



HR-SL-WN-B-NT



HR-SH-WN-B-NT



HR-SL-NW-W-NT



HR-SH-NW-W-NT




HR-SL-NW-B-NT



HR-SH-NW-B-NT

HIERRO

Corp de iluminat liniar LED



HR-SH-NT

