

HIERRO

Corp de iluminat liniar LED










 220-240 AC	 50	 ≥30000	 50000	 Ra 80	
 DALI		 IP 20		 5÷25	
 0,5÷2,5		 0,5m			



HRD-ML-WW-W-PT

HIERRO

Corp de iluminat liniar LED

			 T _c [K]	 TYPE	 [°]		 [lm]	 [mm]
HRD-ML-WW-W-PT	37072	18	3000	raster	X60/Y60	alb	2350	595
HRD-MM-WW-W-PT	37073	23	3000	raster	X60/Y60	alb	2850	595
HRD-MH-WW-W-PT	37074	28	3000	raster	X60/Y60	alb	3300	595
HRD-ML-WW-B-PT	37078	18	3000	raster	X60/Y60	negru	2100	595
HRD-MM-WW-B-PT	37079	23	3000	raster	X60/Y60	negru	2500	595
HRD-MH-WW-B-PT	37080	28	3000	raster	X60/Y60	negru	2900	595
HRD-ML-WN-W-PT	37084	18	3500	raster	X60/Y60	alb	2400	595
HRD-MM-WN-W-PT	37085	23	3500	raster	X60/Y60	alb	2900	595
HRD-MH-WN-W-PT	37086	28	3500	raster	X60/Y60	alb	3350	595
HRD-ML-WN-B-PT	37090	18	3500	raster	X60/Y60	negru	2150	595
HRD-MM-WN-B-PT	37091	23	3500	raster	X60/Y60	negru	2600	595
HRD-MH-WN-B-PT	37092	28	3500	raster	X60/Y60	negru	3000	595
HRD-ML-NW-W-PT	37096	18	4000	raster	X60/Y60	alb	2450	595
HRD-MM-NW-W-PT	37097	23	4000	raster	X60/Y60	alb	3000	595
HRD-MH-NW-W-PT	37098	28	4000	raster	X60/Y60	alb	3450	595
HRD-ML-NW-B-PT	37102	18	4000	raster	X60/Y60	negru	2200	595
HRD-MM-NW-B-PT	37103	23	4000	raster	X60/Y60	negru	2650	595
HRD-MH-NW-B-PT	37104	28	4000	raster	X60/Y60	negru	3050	595

- Materialul carcasei: oțel, material din plastic
- Materialul abajurului: material din plastic



HIERRO

Corp de iluminat liniar LED



HRD-ML-WW-W-PT



HRD-MM-WW-W-PT



HRD-MH-WW-W-PT



HRD-ML-WW-B-PT



HRD-MM-WW-B-PT



HRD-MH-WW-B-PT



HRD-ML-WN-W-PT



HRD-MM-WN-W-PT



HRD-MH-WN-W-PT



HRD-ML-WN-B-PT



HRD-MM-WN-B-PT



HRD-MH-WN-B-PT



HRD-ML-NW-W-PT



HRD-MM-NW-W-PT



HRD-MH-NW-W-PT



HRD-ML-NW-B-PT

HIERRO


Corp de iluminat liniar LED



HRD-MM-NW-B-PT



HRD-MH-NW-B-PT



HRD-M-PT