

## FUTURIO LED DALI 55W 1480mm

Пыленепроницаемый светильник LED



[V] 220-240 AC	[Hz] 50	≥30000	50000	ellipse ≤3x MacAdam	Ra 80	SMD
DALI		IP 65			IK 08	
[mm²] 0,5+2,5	0,5m	CE	EAC	PZH	UK CA	



### FTD1500 55W-840-OPL

	[W]	Tc [K]	TYPE	[°]	[lm]	lm W	[mm]	[°C]	
FTD1500 55W-840-OPL	<b>28658</b>	55	4000	опалевый	X130/Y110	7500	136	1480	-25÷35
FTD1500 55W-840-RYF	<b>28666</b>	55	4000	grooved	X115/Y105	8150	148	1480	-25÷35
FTD1500 55W-840-INT	<b>28668</b>	55	4000	призматический, узкопучковый	X70/Y95	7900	144	1480	-25÷35
FTD1500 55W-840-ASY	<b>28669</b>	55	4000	призматический, асимметричный	X75/Y95	7900	144	1480	-25÷35

- 5 лет Гарантии на условиях гарантийного заявления, доступного на веб-сайте
- Материал корпуса: PC
- Материал плафона: PC



FTD1500 55W-840-OPL



FTD1500 55W-840-RYF




FTD1500 55W-840-INT




FTD1500 55W-840-ASY

## FUTURIO LED DALI 55W 1480mm


Пыленепроницаемый светильник LED




FTD1500 55W-840-OPL



FTD1500 55W-840-RYF



FTD1500 55W-840-INT



FTD1500 55W-840-ASY