

FUTURIO LED DALI 43W 1480mm

Пыленепроницаемый светильник LED



[V] 220-240 AC	[Hz] 50	≥30000	50000	ellipse ≤3x MacAdam	Ra 80	SMD
DALI		IP 65			IK 08	
[mm ²] 0,5+2,5	0,5m	CE	EAC	PZH	UK CA	



FTD1500 43W-840-OPL

	[W]	Tc [K]	TYPE	[°]	[lm]	lm W	[mm]	[°C]	
FTD1500 43W-840-OPL	28862	43	4000	опалевый	X130/Y110	6100	142	1480	-25÷40
FTD1500 43W-840-RYF	28863	43	4000	grooved	X115/Y105	6500	151	1480	-25÷40
FTD1500 43W-840-INT	28864	43	4000	призматический, узкопучковый	X70/Y95	6300	147	1480	-25÷40
FTD1500 43W-840-ASY	28865	43	4000	призматический, асимметричный	X75/Y95	6300	147	1480	-25÷40

- 5 лет Гарантии на условиях гарантийного заявления, доступного на веб-сайте
- Материал корпуса: PC
- Материал плафона: PC



FTD1500 43W-840-OPL



FTD1500 43W-840-RYF




FTD1500 43W-840-INT




FTD1500 43W-840-ASY

FUTURIO LED DALI 43W 1480mm


Пыленепроницаемый светильник LED




FTD1500 43W-840-OPL



FTD1500 43W-840-RYF



FTD1500 43W-840-INT



FTD1500 43W-840-ASY