

## FUTURIO LED 73W 1480mm

Пыленепроницаемый светильник LED



[V] 220-240 AC	[Hz] 50	≥30000	50000	ellipse ≤3x MacAdam	Ra 80	SMD
DALI		IP 65			IK 08	
[mm] 0,5+2,5	0,5m	CE	EAC	UK CA		



### FTHL1500 73W-840-OPL

	[W]	Tc [K]	TYPE	[°]	[lm]	[mm]	[°C]		
FTHL1500 73W-840-OPL	<b>28866</b>	73	4000	опалевый	X130/Y110	9400	129	1480	-25÷35
FTHL1500 73W-840-RYF	<b>28867</b>	73	4000	grooved	X115/Y105	10200	140	1480	-25÷35
FTHL1500 73W-840-INT	<b>28868</b>	73	4000	призматический, узколучковый	X70/Y95	9800	134	1480	-25÷35
FTHL1500 73W-840-ASY	<b>28869</b>	73	4000	призматический, асимметричный	X75/Y95	9800	134	1480	-25÷35

- 5 лет Гарантии на условиях гарантийного заявления, доступного на веб-сайте
- Материал корпуса: PC
- Материал плафона: PC



FTHL1500 73W-840-OPL



FTHL1500 73W-840-RYF




FTHL1500 73W-840-INT




FTHL1500 73W-840-ASY

## FUTURIO LED 73W 1480mm


Пыленепроницаемый светильник LED




FTHL1500 73W-840-OPL



FTHL1500 73W-840-RYF



FTHL1500 73W-840-INT



FTHL1500 73W-840-ASY