

FUTURIO LED 43W 1480mm

Пыленепроницаемый светильник LED



[V] 220-240 AC	[Hz] 50	≥30000	[h] 50000	ellipse ≤3x MacAdam	Ra 80	SMD
DALI		IP 65			IK 08	
[mm] 0,5+2,5	[m] 0,5m	CE	EAC	PZH	UK CA	



FTHT1500 43W-840-OPL

	[W]	Tc [K]	TYPE	[°]	[lm]	[W]	[mm]	[°C]	
FTHT1500 43W-840-OPL	28870	43	4000	опалевый	X130/Y110	6100	142	1480	-25÷50
FTHT1500 43W-840-RYF	28871	43	4000	grooved	X115/Y105	6500	151	1480	-25÷50
FTHT1500 43W-840-INT	28872	43	4000	призматический, узкопучковый	X70/Y95	6300	147	1480	-25÷50
FTHT1500 43W-840-ASY	28873	43	4000	призматический, асимметричный	X75/Y95	6300	147	1480	-25÷50

- 5 лет Гарантии на условиях гарантийного заявления, доступного на веб-сайте
- Материал корпуса: PC
- Материал плафона: PC



FTHT1500 43W-840-OPL



FTHT1500 43W-840-RYF




FTHT1500 43W-840-INT




FTHT1500 43W-840-ASY

FUTURIO LED 43W 1480mm


Пыленепроницаемый светильник LED




FTHT1500 43W-840-OPL



FTHT1500 43W-840-RYF



FTHT1500 43W-840-INT



FTHT1500 43W-840-ASY