

AL-LH-PT

Линейный светодиодный светильник



[V] 220-240 AC	[Hz] 50	≥30000	[h] 50000	ellipse ≤3x MacAdam	Ra 80	SMD
		IP 20		[°C] 5÷25		
[mm²] 1,5÷2,5		0,5m				



AL-LH-NW-MAT-W-PT

	[V]	Tc [K]	TYPE	[°]		[m]	[mm]
AL-LH-NW-MAT-W-PT	34117	52	4000	матовый	X85/Y95	белый	6300 1710
AL-LH-WW-MAT-W-PT	34119	52	3000	матовый	X85/Y95	белый	5600 1710
AL-LH-NW-MPR-W-PT	34121	52	4000	микропризматический	X75/Y90	белый	5800 1710
AL-LH-WW-MPR-W-PT	34123	52	3000	микропризматический	X75/Y90	белый	5150 1710
AL-LH-NW-MAT-B-PT	34129	52	4000	матовый	X85/Y95	черный	6300 1710
AL-LH-WW-MAT-B-PT	34131	52	3000	матовый	X85/Y95	черный	5600 1710
AL-LH-NW-MPR-B-PT	34133	52	4000	микропризматический	X75/Y90	черный	5800 1710
AL-LH-WW-MPR-B-PT	34135	52	3000	микропризматический	X75/Y90	черный	5150 1710
AL-LH-NW-MAT-S-PT	34141	52	4000	матовый	X85/Y95	серебряный	6300 1710
AL-LH-WW-MAT-S-PT	34143	52	3000	матовый	X85/Y95	серебряный	5600 1710
AL-LH-NW-MPR-S-PT	34145	52	4000	микропризматический	X75/Y90	серебряный	5800 1710
AL-LH-WW-MPR-S-PT	34147	52	3000	микропризматический	X75/Y90	серебряный	5150 1710

- 5 лет Гарантии на условиях гарантийного заявления, доступного на веб-сайте
- Материал корпуса: сталь
- Материал плафона: пластмасса

AL-LH-PT

Линейный светодиодный светильник



AL-LH-NW-MAT-W-PT



AL-LH-WW-MAT-W-PT



AL-LH-NW-MPR-W-PT



AL-LH-WW-MPR-W-PT



AL-LH-NW-MAT-B-PT



AL-LH-WW-MAT-B-PT



AL-LH-NW-MPR-B-PT



AL-LH-WW-MPR-B-PT

AL-LH-PT

Линейный светодиодный светильник



AL-LH-NW-MAT-S-PT




AL-LH-WW-MAT-S-PT




AL-LH-NW-MPR-S-PT




AL-LH-WW-MPR-S-PT




AL-LH-NW-MAT-W-PT




AL-LH-WW-MAT-W-PT




AL-LH-NW-MPR-W-PT




AL-LH-WW-MPR-W-PT




AL-LH-NW-MAT-B-PT




AL-LH-WW-MAT-B-PT




AL-LH-NW-MPR-B-PT




AL-LH-WW-MPR-B-PT




AL-LH-NW-MAT-S-PT



AL-LH-WW-MAT-S-PT



AL-LH-NW-MPR-S-PT



AL-LH-WW-MPR-S-PT