

BTL LED

Пржектор для шинопровода



[V] 220-240 AC	[Hz] 50	 ≥30000	 50000	 ellipse ≤ 6x Mackdam	 Ra 90	 COB
		IP 20		 5+25		 340
 90	 0,5m	CE	EAC	UK CA		



BTL 18W-930-W



Model	Power [W]	Beam angle [lm]	Temperature Tc [K]	Beam angle [°]	Color rendering
BTL 18W-930-W	35650	18	1800	3000	15-45 белый
BTL 18W-930-B	35651	18	1750	3000	15-45 черный
BTL 18W-940-W	35652	18	1800	4000	15-45 белый
BTL 18W-940-B	35653	18	1750	4000	15-45 черный
BTL 28W-930-W	35654	28	3000	3000	15-45 белый
BTL 28W-930-B	35655	28	2800	3000	15-45 черный
BTL 28W-940-W	35656	28	3000	4000	15-45 белый
BTL 28W-940-B	35657	28	2800	4000	15-45 черный
BTL 38W-930-W	35658	38	4000	3000	15-45 белый
BTL 38W-930-B	35659	38	3800	3000	15-45 черный
BTL 38W-940-W	35660	38	4000	4000	15-45 белый
BTL 38W-940-B	35661	38	3800	4000	15-45 черный

- 5 лет Гарантии на условиях гарантийного заявления, доступного на веб-сайте
- Материал корпуса: сплав алюминия

BTL LED

Прожектор для шинпровода



BTL 18W-930-W



BTL 18W-930-B



BTL 18W-940-W



BTL 18W-940-B



BTL 28W-930-W



BTL 28W-930-B



BTL 28W-940-W



BTL 28W-940-B

BTL LED

Прожектор для шинпровода



BTL 38W-930-W




BTL 38W-930-B




BTL 38W-940-W




BTL 38W-940-B



BTL 18W



BTL 28W



BTL 38W