


Kanlux



Kanlux AL-ML-NT








- 5-ročná záruka podľa podmienok vyhlásenia o záruke, ktoré je dostupné na webovej stránke



 220-240 AC	 50	 ≥30000	 50000	 ≤3x MacAdam ellipse Ra 80	 SMD
 No dimming	 Grounding	 IP 20	 House	 5÷25	 Packaging
 1,5÷2,5 [mm ²]	 Beam angle	 0,5m	 CE	 EAC	 UKCA



AL-ML-MAT-B-NT

								
AL-ML-NW-MAT-B-NT	33984	25	4000	matné	X85/Y95	čierna	3250	1140
AL-ML-NW-MAT-S-NT	33996	25	4000	matné	X85/Y95	strieborná	3250	1140
AL-ML-NW-MAT-W-NT	33972	25	4000	matné	X85/Y95	biela	3250	1140
AL-ML-NW-MPR-B-NT	33988	25	4000	mikroprizmatický	X75/Y90	čierna	3000	1140
AL-ML-NW-MPR-S-NT	34000	25	4000	mikroprizmatický	X75/Y90	strieborná	3000	1140
AL-ML-NW-MPR-W-NT	33976	25	4000	mikroprizmatický	X75/Y90	biela	3000	1140
AL-ML-NW-RST-B-NT	33992	25	4000	raster	X85/Y85	čierna	3400	1140
AL-ML-NW-RST-W-NT	33980	25	4000	raster	X85/Y85	biela	3850	1140
AL-ML-WW-MAT-B-NT	33986	25	3000	matné	X85/Y95	čierna	2980	1140
AL-ML-WW-MAT-S-NT	33998	25	3000	matné	X85/Y95	strieborná	2980	1140
AL-ML-WW-MAT-W-NT	33974	25	3000	matné	X85/Y95	biela	2980	1140
AL-ML-WW-MPR-B-NT	33990	25	3000	mikroprizmatický	X75/Y90	čierna	2750	1140
AL-ML-WW-MPR-S-NT	34002	25	3000	mikroprizmatický	X75/Y90	strieborná	2750	1140
AL-ML-WW-MPR-W-NT	33978	25	3000	mikroprizmatický	X75/Y90	biela	2750	1140
AL-ML-WW-RST-B-NT	33994	25	3000	raster	X85/Y85	čierna	3250	1140
AL-ML-WW-RST-W-NT	33982	25	3000	raster	X85/Y85	biela	3650	1140
AL-ML5D-NW-RST-B-NT	37572	25	4000	raster	X60/Y60	čierna	3400	1140
AL-ML5D-NW-RST-W-NT	37573	25	4000	raster	X60/Y60	biela	3850	1140
AL-ML5D-WW-RST-B-NT	37574	25	3000	raster	X60/Y60	čierna	3250	1140
AL-ML5D-WW-RST-W-NT	37575	25	3000	raster	X60/Y60	biela	3650	1140



AL-ML-MAT-B-NT



AL-ML-MAT-W-NT



AL-ML-MAT-S-NT



AL-ML-MPR-B-NT



AL-ML-MPR-W-NT




AL-ML-MPR-S-NT



AL-ML-RST-B-NT



AL-ML-RST-W-NT



AL-ML-NT

Príslušenstvo

32540

ALIN CORD 1F-W

Napájací kábel pre lineárne svietidla ALIN, 1-fázový, biely, 150cm



32541

ALIN CORD 1F-B

Napájací kábel pre lineárne svietidla ALIN, 1-fázový, čierny, 150cm



32542

ALIN CORD 1F-SR

Napájací kábel pre lineárne svietidla ALIN, 1-fázový, strieborný, 150cm



07871

ROPE-NT 150 SINGLE

ROPE-NT 150 SINGLE ocelové lanko (jedno) na zavesenie svietidla, 2 ks v balení



25979

KLOSZ MPR AL 23W/33W

Difúzor MPR pre svietidla ALIN, KLOSZ MPR AL 23W/33W, (25979)

