


## 23198 KRD6-4/100/30-A

Residual-current circuit breaker, 4P

5905339231987



Residual current circuit breaker: is used for additional protection against electric shock, designed for work in sinusoidal alternating current circuits (AC type) and sinusoidal alternating and pulsating current with DC component (A type).

### GENERAL DATA:

**Colour:** white

**Place of assembly:** na szynę TH35

**Norm:** PN-EN 61008-1

**Length [mm]:** 75

**Width [mm]:** 70

**Height [mm]:** 82

### TECHNICAL DATA:

**Rated voltage [V]:** 400 AC

**Rated current [A]:** 100

**Rated frequency [Hz]:** 50

**Ambient temperature range to which the product can be exposed:** -25÷40

**Range of sections of wires used [mm<sup>2</sup>]:** do 35

**Residual-current protection type:** A

**Number of modules:** 4

**Differential-rated current [mA]:** 30

**IP class:** 20

**Rated insulation voltage UI [V]:** 400

**Number of poles:** 4

### LOGISTIC DATA:

**Unit of measurement:** unit

**Packaging method:** 30

**Number of units in the secondary packaging:** 1

**Number of units in the packaging:** 30

**Net unit weight [g]:** 420

**Grammage [g]:** 390.67

**Length of a unit pack [cm]:** 9

**Width of a unit pack [cm]:** 8

**Height of a unit pack [cm]:** 8

**Weight of a cardboard box [kg]:** 11.7201

**Width of a cardboard box [cm]:** 28

**Height of a cardboard box [cm]:** 18.5

**Length of a cardboard box [cm]:** 47

## 23198 KRD6-4/100/30-A

---

Residual-current circuit breaker, 4P

| Volume of a cardboard box [m<sup>3</sup>]: 0.024346