


23226 KRD6-2/40/100-A

Residual-current circuit breaker, 2P

5905339232267



Residual current circuit breaker: is used for additional protection against electric shock, designed for work in sinusoidal alternating current circuits (AC type) and sinusoidal alternating and pulsating current with DC component (A type).

GENERAL DATA:

Colour: white

Place of assembly: na szynę TH35

Norm: PN-EN 61008-1

Length [mm]: 75

Width [mm]: 35

Height [mm]: 81

TECHNICAL DATA:

Rated voltage [V]: 230 AC

Rated current [A]: 40

Rated frequency [Hz]: 50

Ambient temperature range to which the product can be exposed: -25÷40

Range of sections of wires used [mm²]: do 35

Residual-current protection type: A

Number of modules: 2

Differential-rated current [mA]: 100

IP class: 20

Rated insulation voltage UI [V]: 400

Number of poles: 2

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 60

Number of units in the secondary packaging: 1

Number of units in the packaging: 60

Net unit weight [g]: 206

Grammage [g]: 231.5

Gross unit weight [g]: 224

Length of a unit pack [cm]: 9

Width of a unit pack [cm]: 4

Height of a unit pack [cm]: 8.5

Weight of a cardboard box [kg]: 13.89

Width of a cardboard box [cm]: 27.5

23226 KRD6-2/40/100-A

Residual-current circuit breaker, 2P

Height of a cardboard box [cm]: 18.5

Length of a cardboard box [cm] : 47

Volume of a cardboard box [m³]: 0.023911