

23239 KMI-R-3/125A

Modular switch disconnector

5905339232397



GENERAL DATA:

Utilisation category: AC-22A / AC-23A

Place of application: Indoors

Norm: PN-EN 60947-3

Length [mm]: 81

Width [mm]: 54

Height [mm]: 98

TECHNICAL DATA:

Rated voltage [V]: 415 AC

Rated current [A]: 125

Rated frequency [Hz]: 50

Connection type: Terminal block

Range of sections of wires used [mm²]: 1-25

Control type: mechaniczne

Number of modules: 3

IP class: 20

Rated insulation voltage UI [V]: 800

Rated impulse withstand voltage Uimp [V]: 6000

Rated operational current Ie [A]: 125 (AC-22A) / 80 (AC-23A)

Number of poles: 3

Thermal current Ith [A]: 125

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 40

Number of units in the secondary packaging: 1

Number of units in the packaging: 40

Net unit weight [g]: 260

Grammage [g]: 294.25

Length of a unit pack [cm]: 5.7

Width of a unit pack [cm]: 10

Height of a unit pack [cm]: 8.6

Weight of a cardboard box [kg]: 11.77

Width of a cardboard box [cm]: 23

Height of a cardboard box [cm]: 19

Length of a cardboard box [cm]: 51.5

Volume of a cardboard box [m³]: 0.022506

23239 KMI-R-3/125A

Modular switch disconnecter

