

23258 KCS-40A/4P

Przełącznik instalacyjny 5905339232588











GENERAL DATA:

Utilisation category: AC-22A Place of application: Indoors

Norm: PN-EN 60947-3 Length [mm]: 76 Width [mm]: 70.4 Height [mm]: 88.5

TECHNICAL DATA:

Rated voltage [V]: 230/400 AC

Rated current [A]: 40 Rated frequency [Hz]: 50

Ambient temperature range to which the product can be

exposed: -25+40

Connection type: Terminal block

Range of sections of wires used [mm²]: max 16

Control type: mechaniczne Control type: I - 0 - II Number of modules: 4 Tightening force [Nm]: 1,2

IP class: 20

Electrical endurance: 2000 Number of poles: 4 (12)

LOGISTIC DATA:

Unit of measurement: unit Packaging method: 30

Number of units in the secondary packaging: 1


Number of units in the packaging: 30

Net unit weight [g]: 298 Grammage [g]: 336.67

Length of a unit pack [cm]: 7.5 Width of a unit pack [cm]: 9 Height of a unit pack [cm]: 8.1

Weight of a cardboard box [kg]: 10.1001
Width of a cardboard box [cm]: 25
Height of a cardboard box [cm]: 19.5
Length of a cardboard box [cm]: 50

Volume of a cardboard box [m³]: 0.024375









23258 KCS-40A/4P

Przełącznik instalacyjny





We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.

