

## 23456 ALER MINI-B/B

PIR motion sensor 5905339234568









Colour: black Place of assembly: wall mounted Place of application: Indoors and outdoors Micro-interval between relay contacts: yes Length [mm]: 80 Width [mm]: 80 Height [mm]: 67

## TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Class of protection against electric shock : II Material: plastic Ambient temperature range to which the product can be exposed: -20÷40 Sensor type: PIR Connection type: Bolt terminal block Range of sections of wires used [mm<sup>2</sup>]: 1÷2,5 Sensor-operation time [second-minute]: 10-15 sensor working angle [°]: H140/V45 Maximum operating time [min]: 15 Minimum operating time[s]: 10 Maximum power [VA]: 800 Illumination-level setpoint by which the sensor detects movement [lx]: 3-2000 IP class: 44 Sensor range[m]: max 6,5

## LOGISTIC DATA:

Unit of measurement: unit Packaging method: 50 Number of units in the secondary packaging: 1 Number of units in the packaging: 50 Net unit weight [g]: 100 Grammage [g]: 142.6 Gross unit weight [g]: 134 Length of a unit pack [cm]: 8.5 Width of a unit pack [cm]: 6 Height of a unit pack [cm]: 8.5

Date of issue: 04.02.2025, 13:16 We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample. Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com



## 23456 ALER MINI-B/B

PIR motion sensor

Weight of a cardboard box [kg]: 7.13 Width of a cardboard box [cm]: 35 Height of a cardboard box [cm]: 20 Length of a cardboard box [cm] : 44 Volume of a cardboard box [m<sup>3</sup>]: 0.0308

