


23629 KDB-S36P

KDB-series distribution board

5905339236296



KDB series switchboards meeting the requirement for heat resistance at the temperature of 650°C, can be used on non-flammable surfaces only (e.g. full solid walls made of non-combustible materials). They cannot be used on flammable surfaces (e.g. plasterboard, wood boards, etc.), on the so-called "hollow walls" or on technical sections

GENERAL DATA:

Colour: white
Door colour: white
Place of assembly: wall mounted
Norm: PN-EN 62208
Length [mm]: 410
Width [mm]: 109
Height [mm]: 294

TECHNICAL DATA:

Rated voltage [V]: 230/400 AC
Rated current [A]: 63
Rated frequency [Hz]: 50
Class of protection against electric shock : II
Material: plastic
Number of modules: 2x18P
Temperature resistance [°C]: 650
IK class: 07
IP class: 30
number of rows: 2
Ilość zacisków N/PE: (6+6+6)x2

LOGISTIC DATA:

Unit of measurement: unit
Packaging method: 5
Number of units in the secondary packaging : 1
Number of units in the packaging: 5
Net unit weight [g]: 1644
Grammage [g]: 2096
Gross unit weight [g]: 1910
Length of a unit pack [cm]: 31
Width of a unit pack [cm]: 11.5
Height of a unit pack [cm]: 42.5
Weight of a cardboard box [kg]: 10.48

23629 KDB-S36P

KDB-series distribution board

Width of a cardboard box [cm]: 32

Height of a cardboard box [cm]: 44

Length of a cardboard box [cm] : 58.5

Volume of a cardboard box [m³]: 0.082368