# Kanlux

## 26384 TIBERI DRV C&P M500MA

## LED power supply unit 5905339263841









Kanlux TIBERI CCT are reliable flush-mounted luminaires ideal for suspended ceilings, perfect for lighting communication routes, offices and commercial spaces. They are characterized by a durability of 50,000 hours and a luminous efficacy of up to 120 Im/W. Thanks to the high color rendering index (CRI > 90), the light faithfully reproduces colors, and the ability to choose the color temperature (3000K, 3500K, 4000K) allows you to match the lighting to the character of the interior. The luminaires also offer power regulation (Power Switch) in the range of: 15-21 W or 23-29 W. Increased tightness (IP44/20) provides protection against dust, dirt and water splashes, making the luminaires suitable for demanding environments. The lack of a power supply in the set allows you to choose the on-off model (500 mA, 700 mA) or DALI (max. 700 mA). Kanlux TIBERI CCT are available in white and black, and a 5-year warranty confirms their quality and reliability. This is a modern solution that combines functionality with aesthetics.

#### GENERAL DATA:

Colour: white Place of application: Indoors Compatible with a dimmer: no Sprawność zasilacza [%]: 90 Length [mm]: 133 Width [mm]: 50 Height [mm]: 26 The power supply dedicated to the LED fixtures [index] : 26380, 26381

#### **TECHNICAL DATA:**

Rated voltage [V]: 220-240 ACRated current [A]: 0,18Rated frequency [Hz]: 50λ: 0,95Rated power [W]: 14,7-21Maximum power [W]: 21Class of protection against electric shock : IIMaterial: plasticConnection type: Self-clamping block

Date of issue: 06.02.2025, 15:22 We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample. Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com



### 26384 TIBERI DRV C&P M500MA

### LED power supply unit

Supply-cord type: direct current Thermal protection: 110°C Maximum temperature Ta [°C]: 45 Input voltage - PRI [V]: 220-240 Output voltage - SEC [V]: 27-42 DC Output current - sec [ma]: 350-500 IP class: 20 Tc [°C]: 75

#### LOGISTIC DATA:

Unit of measurement: unit Packaging method: 70 Number of units in the secondary packaging: 1 Number of units in the packaging: 70 Net unit weight [g]: 110 Grammage [g]: 138.43 Gross unit weight [g]: 132 Length of a unit pack [cm]: 14.5 Width of a unit pack [cm]: 6 Height of a unit pack [cm]: 3 Weight of a cardboard box [kg]: 9.6901 Width of a cardboard box [cm]: 32 Height of a cardboard box [cm]: 23 Length of a cardboard box [cm]: 23 Length of a cardboard box [cm]: 34 Volume of a cardboard box [m<sup>3</sup>]: 0.025024