

## 26385 TIBERI DRV C&P M700MA

LED power supply unit

5905339263858



Kanlux TIBERI CCT are reliable flush-mounted luminaires ideal for suspended ceilings, perfect for lighting communication routes, offices and commercial spaces. They are characterized by a durability of 50,000 hours and a luminous efficacy of up to 120 lm/W. Thanks to the high color rendering index (CRI > 90), the light faithfully reproduces colors, and the ability to choose the color temperature (3000K, 3500K, 4000K) allows you to match the lighting to the character of the interior. The luminaires also offer power regulation (Power Switch) in the range of: 15–21 W or 23–29 W. Increased tightness (IP44/20) provides protection against dust, dirt and water splashes, making the luminaires suitable for demanding environments. The lack of a power supply in the set allows you to choose the on-off model (500 mA, 700 mA) or DALI (max. 700 mA). Kanlux TIBERI CCT are available in white and black, and a 5-year warranty confirms their quality and reliability. This is a modern solution that combines functionality with aesthetics.

### GENERAL DATA:

**Colour:** white

**Place of application:** Indoors

**Compatible with a dimmer:** no

**Sprawność zasilacza [%]:** 88

**Length [mm]:** 133

**Width [mm]:** 50

**Height [mm]:** 26

**The power supply dedicated to the LED fixtures [index]:** 26382, 26383

### TECHNICAL DATA:

**Rated voltage [V]:** 220-240 AC

**Rated current [A]:** 0,22

**Rated frequency [Hz]:** 50

$\lambda$ : 0,95

**Rated power [W]:** 23,1-29,4

**Maximum power [W]:** 29,4

**Class of protection against electric shock:** II

**Material:** plastic

**Connection type:** Self-clamping block



## 26385 TIBERI DRV C&P M700MA

LED power supply unit

**Supply-cord type:** direct current  
**Thermal protection:** 110°C  
**Maximum temperature Ta [°C]:** 45  
**Input voltage - PRI [V]:** 220-240  
**Output voltage - SEC [V]:** 27-42  
**Output current - sec [ma]:** 550-700  
**IP class:** 20  
**Tc [°C]:** 75

### LOGISTIC DATA:

**Unit of measurement:** unit  
**Packaging method:** 70  
**Number of units in the secondary packaging :** 1  
**Number of units in the packaging:** 70  
**Net unit weight [g]:** 124  
**Grammage [g]:** 150.34  
**Gross unit weight [g]:** 146  
**Length of a unit pack [cm]:** 14.5  
**Width of a unit pack [cm]:** 6  
**Height of a unit pack [cm]:** 3  
**Weight of a cardboard box [kg]:** 10.5238  
**Width of a cardboard box [cm]:** 32  
**Height of a cardboard box [cm]:** 23  
**Length of a cardboard box [cm] :** 34  
**Volume of a cardboard box [m³]:** 0.025024