


28987 ONTEC G E1E180NMATW

Emergency lighting LED

5902052563616



Emergency or anti-panic lighting is used in open space rooms to prevent panic. It allows you to reach a place where you can see the marked escape route as well as for the illumination of the escape route itself, depending on the prism used in the fixture.

GENERAL DATA:

Colour: white

Place of assembly: ceiling mounted

Place of application: Indoors

Length [mm]: 250

Width [mm]: 29

Height [mm]: 194

Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Rated power [W]: 1,2

Rated power (LED) [W]: 0.9

Class of protection against electric shock: II

Lampshade material: plastic

Diode type: LED SMD

Colour temperature: cold white

Correlated colour temperature [K]: 5000

Ambient temperature range to which the product can be exposed: 10÷35

Battery (type): LiFePO₄/C

Battery (parameters): 3,2V 1,5Ah

Operating mode: emergency

Application: marking of escape routes

Fail-safe working time [h]: 3

Automatic test: yes

Enclosure material: plastic

Connection type: Self-clamping block

IP class: 20

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 1

Gross unit weight [g]: 464

28987 ONTEC G E1E180NMATW

Emergency lighting LED

ACCESSORIES

33813

ZESt MONT OG00 W

