

29312 CHIRO GU10 DTL-W

Ceiling-mounted spotlight fitting

5905339293121




MO
DE
RN
design

DE
SI
GN
unique



Ø 70



Kanlux CHIRO GU10, is a completely new category of decorative lighting. It is the ceiling-mounted lamp which can be mounted in a suspended ceiling just like an typical spotlight fitting. Unique design and assembly of this lamp are its largest assets.

GENERAL DATA:

Colour: white

Necessity of using self-shielding lamps: yes

Place of assembly: Recessed mount in the ceiling

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

The product is not suitable to be covered with a heat-insulating material: yes

Assembly hole [mm]: Ø70

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Maximum power [W]: max 10

Class of protection against electric shock: I

Light source: PAR16

Light source included: no

Cap: GU10

Ambient temperature range to which the product can be exposed: 5÷25

Enclosure material: aluminum alloy

Connection type: Bolt terminal block

Range of sections of wires used [mm²]: 0,75-1,5

The fixture is movable horizontally [°]: 340

Lighting-fixture angle regulation: in one axis

Lighting-fixture angle regulation [°]: 90

IP class: 20

LOGISTIC DATA:

Packaging method: 20

Number of units in the secondary packaging: 1

Number of units in the packaging: 20

Number of units per layer on a pallet: 140

Net unit weight [g]: 400

Grammage [g]: 497.5

Length of a unit pack [cm]: 10

Width of a unit pack [cm]: 8.5

Height of a unit pack [cm]: 15

Weight of a cardboard box [kg]: 9.95

Width of a cardboard box [cm]: 21

29312 CHIRO GU10 DTL-W

Ceiling-mounted spotlight fitting



Height of a cardboard box [cm]: 32.5

Length of a cardboard box [cm] : 44.5

Volume of a cardboard box [m³]: 0.030371