

31169 BAREV ECO 36W 6060NW

Recessed-mounted LED panel

8595665311698



GENERAL DATA:

Colour: white
Place of assembly: Recessed mount in the ceiling
Place of application: Indoors
Minimum distance from the illuminated object : 0,5m
Compatible with a dimmer: no
The product is not suitable to be covered with a heat-insulating material: yes
Feeder included: yes
Length [mm]: 595
Width [mm]: 595
Height [mm]: 30
Mercury content in the lamp [mg] : 0
Integrated LED light source : yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC
Rated frequency [Hz]: 50
Maximum power [W]: 36
Class of protection against electric shock : I
Lampshade material: plastic
Diode type: LED SMD
Luminous flux of the light fitting [lm]: 4320
Useful luminous flux of the light source Φ_{use} [lm] : 6 x 920
Useful luminous flux of the light source Φ_{use} [lm] : in sphere (360°)
Colour temperature: white
Correlated colour temperature [K]: 4000
Colour consistency in McAdam ellipses : 6
Colour rendering index: 80
Service life [h]: 25000
Number of on/off cycles: ≥ 10000
Lighting angle [°]: 110
Luminous efficiency of the lamp [lm/W]: 120
Ambient temperature range to which the product can be exposed: 5÷25
Enclosure material: steel
Connection type: Free cable ends
Wire diameter [mm²]: 0,75
IP class: 20


LOGISTIC DATA:

Unit of measurement: unit



31169 BAREV ECO 36W 6060NW

Recessed-mounted LED panel



Packaging method: 10

Number of units in the secondary packaging: 1

Number of units in the packaging: 10

Net unit weight [g]: 1020

Grammage [g]: 1173

Gross unit weight [g]: 1046

Length of a unit pack [cm]: 69.5

Width of a unit pack [cm]: 69.5

Height of a unit pack [cm]: 3

Weight of a cardboard box [kg]: 11.73

Width of a cardboard box [cm]: 37

Height of a cardboard box [cm]: 62

Length of a cardboard box [cm]: 60

Volume of a cardboard box [m³]: 0.13764

