

33226 EMIRES LED W

LED desk lamp

5905339332264





















Kanlux EMIRES LED is an extremely elegant desk lamp. Featuring a dual pivot arm adjustment and a porous texture that adds unparalleled style to it. Kanlux EMIRES has two housing colours to choose from (black mat and white mat) and three lighting colours (WW 3000K, NW 4000K, CW 6000K), as well as smooth light brightness regulation feature. Kanlux EMIRES LED desk lamp conveniently combines all functions in one button: turning on the lamp, changing the light colour and changing the brightness level. The set includes a power supply unit and a power cord.

GENERAL DATA:

Colour: white

Place of assembly: On the floor Place of application: Indoors

Minimum distance from the illuminated object: 0,1m Possibility of dimming only with help of an internal

electronic system: yes

Compatible with a dimmer: no

On switch: yes Length [mm]: 150 Width [mm]: 120

Height MAX [mm]: 550

Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Maximum power [W]: max 5,5

Class of protection against electric shock: ||

Lampshade material: plastic

Diode type: LED SMD

Luminous flux [lm]: max 250

Useful luminous flux of the light source **Quse** [lm]: 360 Useful luminous flux of the light source **Quse** [lm]: in wide

cone (120°)

Colour temperature: Warm white, white, cold white **Correlated colour temperature [K]**: 4000/6000/3000

Colour consistency in McAdam ellipses: ≤6

Colour rendering index: 80 Service life [h]: 25000

Number of on/off cycles: ≥15000

Luminous efficiency of the lamp [lm/W]: max 45

Enclosure material: plastic

Connection type: Cable terminated with a plug

Wire length [m]: 1

Date of issue: 15.11.2022, 01:27


We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.





33226 EMIRES LED W

LED desk lamp





Lamp-heating time [s]: <1 Lamp-ignition time [s]: <0,5

The fixture is movable vertically [°]: 180

IP class: 20

LOGISTIC DATA:

Packaging method: 20


Number of units in the secondary packaging: 1

Number of units in the packaging: 20

Net unit weight [g]: 614 Grammage [g]: 802.5

Length of a unit pack [cm]: 13.5 Width of a unit pack [cm]: 6 Height of a unit pack [cm]: 35

Weight of a cardboard box [kg]: 16.05 Width of a cardboard box [cm]: 32.5 Height of a cardboard box [cm]: 38 Length of a cardboard box [cm]: 55.5 Volume of a cardboard box [m³]: 0.068543



We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.

