


33340 BENO 24W NW-O-W

Ceiling-mounted LED light fitting

5905339333407



Kanlux BENO luminaries that's unique design and unique light effect. They were created on the basis of individual order of Kanlux, and their designs were registered by us at the patent office. Kanlux BENO LED also provides high weather resistance (IP54), quick and easy installation on the ceiling or wall, and Beno is equipped with the adjustable movement sensor (in versions -SE). Kanlux BENO LED is a multifunctional fitting, which due to its design and its technical aspects, we can apply practically anywhere.

GENERAL DATA:


Colour: white
Place of assembly: wall mounted, ceiling mounted
Place of application: Indoors and outdoors
Minimum distance from the illuminated object: 0,5m
Compatible with a dimmer: no
Height [mm]: 55
Diameter [mm]: 260
Mercury content: no
Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC
Rated frequency [Hz]: 50
Maximum power [W]: 24
Class of protection against electric shock: II
Lampshade material: plastic
Diode type: LED SMD
Luminous flux of the light fitting [lm]: 2060
Useful luminous flux of the light source Φ_{use} [lm]: 2900
Useful luminous flux of the light source Φ_{use} [lm]: in sphere (360°)
Colour temperature: white
Correlated colour temperature [K]: 4000
Colour consistency in McAdam ellipses: ≤ 6
Colour rendering index: 80
Service life [h]: 20000
Luminous-flux-retention factor at the end of rated service life: L70B50
Number of on/off cycles: ≥ 20000
Lighting angle [°]: 110
Luminous efficiency of the lamp [lm/W]: 86
Ambient temperature range to which the product can be exposed: -15÷35

33340 BENO 24W NW-O-W

Ceiling-mounted LED light fitting



Enclosure material: plastic

Connection type: Self-clamping block

Range of sections of wires used [mm²]: 0,5÷1,5

Lamp-heating time [s]: ≤1

Lamp-ignition time [s]: ≤0,5

IP class: 54

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 10

Number of units in the secondary packaging : 1

Number of units in the packaging : 10

Net unit weight [g]: 554

Grammage [g]: 760

Length of a unit pack [cm]: 26.5

Width of a unit pack [cm]: 6

Height of a unit pack [cm]: 26.5


Weight of a cardboard box [kg]: 7.6

Width of a cardboard box [cm]: 33

Height of a cardboard box [cm]: 29

Length of a cardboard box [cm] : 55

Volume of a cardboard box [m³]: 0.052635



33340 BENO 24W NW-O-W

Ceiling-mounted LED light fitting

KANLUX S.A. (kat 33340) BENO 24W NW-O-W / LDC (Polar)

Luminaire: KANLUX S.A. (kat 33340) BENO 24W NW-O-W
Lamps: 1 x BENO 24W NW-O-W

