

34326 ALD-MM-NW-MAT-S-PT

Linear LED luminaire


5905339343260













GENERAL DATA:

Colour: silver

Place of assembly: Recessed mount in the ceiling

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Compatible with a dimmer: DALI Fixture lighting direction: down

Length [mm]: 1150 Width [mm]: 83 Height [mm]: 65

Integrated LED light source: yes

Version for connection in line [initial element] LF: 34613 (PT)
Version for connection in line [central element] LM: 34757 (PT)
Version for connection in line [final element] LL: 34901 (PT)
Explanation of markings and signs used: (PT) - do wbudowania

w sufit

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Maximum power [W]: 29

Class of protection against electric shock:

Lampshade material: plastic Diode type: LED SMD Luminous flux [lm]: 3900 Colour temperature: white

Correlated colour temperature [K]: 4000 Colour consistency in McAdam ellipses: ≤3

Colour rendering index: 80 Service life [h]: 50000

Luminous-flux-retention factor at the end of rated service life :

L90B10

Number of on/off cycles: ≥30000 Lighting angle [°]: X85/Y95

Luminous efficiency of the lamp [lm/W]: 134

Ambient temperature range to which the product can be

exposed: 5÷25 Shade type: matt

Enclosure material: steel

Connection type: Self-clamping block

Range of sections of wires used [mm²]: $0.5 \div 2.5$

Lamp-heating time [s]: ≤ 1 Lamp-ignition time [s]: ≤ 0.5

Date of issue: 03.03.2023, 02:46





34326 ALD-MM-NW-MAT-S-PT

Linear LED luminaire

IP class: 20

LOGISTIC DATA:

Unit of measurement: unit Packaging method: 1

Number of units in the secondary packaging: 1

Number of units in the packaging: 1

Net unit weight [g]: 1574 Grammage [g]: 1910

Length of a unit pack [cm]: 136 Width of a unit pack [cm]: 11 Height of a unit pack [cm]: 7

Weight of a cardboard box [kg]: 1.91
Width of a cardboard box [cm]: 11
Height of a cardboard box [cm]: 7
Length of a cardboard box [cm]: 136
Volume of a cardboard box [m³]: 0.010472

ADDITIONAL INFORMATION:

• 5 years Warranty under the terms of the warranty statement, available on our website

