


35005 STIVI LED 10W-NW-O-SE

Ceiling-mounted LED light fitting

5905339350053



IP
65



The Kanlux STIVI LED ceiling light will provide you with lighting where standard luminaires may fail. It is characterised by high luminous efficacy of 130lm/W, a high level of protection - IP65 and impact protection rating of IK08. Kanlux STIVI LED luminaire can be used outdoors (on balconies, terraces, patios, open arbours), in corridors and staircases, as well as in places with increased humidity (laundry rooms, changing rooms and passageways at swimming pools). Additional advantages include: 5-year warranty and 50,000 hours of light source life in the luminaire, as well as the option of choosing a version with a motion sensor. We recommend it as a high-end investment product or for professional domestic use.

GENERAL DATA:

Colour: white

Place of assembly: wall mounted, ceiling mounted

Place of application: Indoors and outdoors

Micro-interval between relay contacts: yes

Minimum distance from the illuminated object: 0,5m

Possibility of fixture-loop-through connection: yes

Compatible with a dimmer: no

Wykrywanie ruchu: yes

Height [mm]: 62

Diameter [mm]: 220

Sensitivity regulation: yes

Mercury content: no

Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Maximum power [W]: 10

Class of protection against electric shock: II

Lampshade material: PC

Diode type: LED SMD

Luminous flux of the light fitting [lm]: 1200

Useful luminous flux of the light source Φ_{use} [lm]: 1500

Colour temperature: white

Correlated colour temperature [K]: 4000

Colour consistency in McAdam ellipses: 6

Colour rendering index: 80

Service life [h]: 50000

35005 STIVI LED 10W-NW-O-SE

Ceiling-mounted LED light fitting



Luminous-flux-retention factor at the end of rated service life :

L70B50

Number of on/off cycles: ≥30000

Lighting angle [°]: 110

Luminous efficiency of the lamp [lm/W]: 120

Ambient temperature range to which the product can be exposed: -20÷40

Enclosure material: PC

Sensor type: microwave

Connection type: Self-clamping block

Range of sections of wires used [mm²]: 0,5-2,5

Sensor-operation time [second-minute]: 5-10

Lamp-heating time [s]: ≤1

Lamp-ignition time [s]: ≤0,5

Sensor-operation frequency [MHz]: 5800

sensor working angle [°]: H360

Illumination-level setpoint by which the sensor detects movement [lx]: 2/10/50/off

IK class: 08

IP class: 65

Sensor range[m]: max 3

Kształt: round

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 8

Number of units in the secondary packaging : 1

Number of units in the packaging: 8

Net unit weight [g]: 544

Grammage [g]: 706.25

Gross unit weight [g]: 640

Length of a unit pack [cm]: 22.5

Width of a unit pack [cm]: 6.5

Height of a unit pack [cm]: 23

Weight of a cardboard box [kg]: 5.65

Width of a cardboard box [cm]: 26

Height of a cardboard box [cm]: 25.5

Length of a cardboard box [cm]: 47

Volume of a cardboard box [m³]: 0.031161

ADDITIONAL INFORMATION:

- 5 years Warranty under the terms of the warranty statement, available on our website