

36515 TAVO LED DL 5W-NW



Downlight fitting

5905339365156

IP
44/20



75x75



Kanlux TAVO LED is a family of flush-mounted downlights. They are available in two shapes (round and square) and 5 wattages - from 5W to 24W. Kanlux TAVO LED downlights are characterised by a minimalist, Scandinavian design. Additional advantages are their IP44/20 tightness, as well as the possibility of surface mounting the 12W and 18W models in the Kanlux TAVO FRAME.

GENERAL DATA:

Colour: white

Place of assembly: Recessed mount in the ceiling

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Compatible with a dimmer: no

The product is not suitable to be covered with a heat-insulating material: yes

Length [mm]: 95

Width [mm]: 95

Height [mm]: 26

Assembly hole [mm]: 75x75

Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Maximum power [W]: 5

Class of protection against electric shock: II

Lampshade material: plastic

Diode type: LED SMD

Luminous flux [lm]: 400

Colour temperature: white

Correlated colour temperature [K]: 4000

Colour consistency in McAdam ellipses: ≤ 6

Colour rendering index: 80

Service life [h]: 25000

Number of on/off cycles: ≥ 15000

Lighting angle [°]: 120

Luminous efficiency of the lamp [lm/W]: 80

Ambient temperature range to which the product can be exposed: 5÷25

Enclosure material: plastic

Connection type: Free cable ends

Wire length [m]: 0.1

Lamp-heating time [s]: ≤ 1

Lamp-ignition time [s]: $\leq 0,5$

IP class: 44/20

Downlight fitting

LOGISTIC DATA:


Packaging method: 1

ACCESSORIES:

36520 TAVO FRAME DO 12W Ramka do montażu natynkowego downlightów Kanlux TAVO LED.



36521 TAVO FRAME DO 18W Ramka do montażu natynkowego downlightów Kanlux TAVO LED.



36522 TAVO FRAME DL 12W Ramka do montażu natynkowego downlightów Kanlux TAVO LED.



36523 TAVO FRAME DL 18W Ramka do montażu natynkowego downlightów Kanlux TAVO LED.

