


Linear LED luminaire

5905339370914



HIERRO is a family of fixtures produced at the Kanlux Factory. The minimalist and elegant form fits into the latest trends in architectural design. The stylish solution is widely used in modern offices, shops, and loft spaces as basic, complementary or accent lighting. The great advantages of HIERRO luminaires are: variety of available control and installation methods, low UGR coefficient, high luminous efficiency, ability to adapt to specific lighting projects and 5-year warranty. This allows you to create energy-saving and modern lighting systems that provide attractive lighting effects.

GENERAL DATA:

Colour: black

Place of assembly: Recessed mount in the ceiling

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Compatible with a dimmer: DALI

Fixture lighting direction: down

Length [mm]: 595

Width [mm]: 70

Height [mm]: 52

Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Maximum power [W]: 23

Class of protection against electric shock: I

Lampshade material: plastic

Diode type: LED SMD

Luminous flux [lm]: 2600

Correlated colour temperature [K]: 3500

Colour consistency in McAdam ellipses: ≤6

Colour rendering index: 80

Service life [h]: 50000

Luminous-flux-retention factor at the end of rated service life: L90B10

Number of on/off cycles: ≥30000

Lighting angle [°]: X60/Y60

Luminous efficiency of the lamp [lm/W]: 113

Ambient temperature range to which the product can be exposed: 5÷25

Shade type: louvre / black

Enclosure material: steel, plastic

37091 HRD-MM-WN-B-PT

Linear LED luminaire



Connection type: Self-clamping block

Range of sections of wires used [mm²]: 0,5÷2,5

IP class: 20

UGR: <17

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 1

Number of units in the secondary packaging: 1

Number of units in the packaging: 1

Net unit weight [g]: 1050

Grammage [g]: 1230

Weight of a cardboard box [kg]: 1.23