

37317 NIFU LED17,8W NW W/BR

Ceiling-mounted LED light fitting

5905339373175



GENERAL DATA:


Colour: biały / brąz
Place of assembly: ceiling mounted
Place of application: Indoors
Minimum distance from the illuminated object: 0,5m
Compatible with a dimmer: no
Height [mm]: 66
Diameter [mm]: 430
Mercury content: no
Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC
Rated frequency [Hz]: 50
Maximum power [W]: 17,8
Class of protection against electric shock: I
Lampshade material: plastic
Light source: LED
Diode type: LED SMD
Luminous flux [lm]: 1320
Useful luminous flux of the light source Φ_{use} [lm]: 2300
Useful luminous flux of the light source Φ_{use} [lm]: in sphere (360°)
Colour temperature: white
Correlated colour temperature [K]: 4000
Colour consistency in McAdam ellipses: 6
Colour rendering index: 80
Service life [h]: 25000
Number of on/off cycles: ≥ 20000
Lighting angle [°]: 120
Luminous efficiency of the lamp [lm/W]: 74
Ambient temperature range to which the product can be exposed: 5÷25
Enclosure material: Metal
Connection type: Bolt terminal block
Range of sections of wires used [mm²]: 1,5
IP class: 20

LOGISTIC DATA:

Unit of measurement: unit
Packaging method: 10
Number of units in the secondary packaging: 1
Number of units in the packaging: 10



37317 NIFU LED17,8W NW W/BR

Ceiling-mounted LED light fitting



Net unit weight [g] : 1050

Grammage [g] : 1539.2

Gross unit weight [g] : 1428

Length of a unit pack [cm] : 45

Width of a unit pack [cm] : 9

Height of a unit pack [cm] : 45

Weight of a cardboard box [kg] : 15.392

Width of a cardboard box [cm] : 47

Height of a cardboard box [cm] : 48

Length of a cardboard box [cm] : 93

Volume of a cardboard box [m³] : 0.209808