

37319 NIFU LED17,8W NW W/B

Ceiling-mounted LED light fitting

5905339373199



GENERAL DATA:

Colour: white / black

Place of assembly: ceiling mounted

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Compatible with a dimmer: no

Height [mm]: 66

Diameter [mm]: 430

Mercury content: no

Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Maximum power [W]: 17,8

Class of protection against electric shock: I

Lampshade material: plastic

Light source: LED

Diode type: LED SMD

Luminous flux [lm]: 1280

Useful luminous flux of the light source Φ_{use} [lm]: 2300

Useful luminous flux of the light source Φ_{use} [lm]: in sphere (360°)

Colour temperature: white

Correlated colour temperature [K]: 4000

Colour consistency in McAdam ellipses: 6

Colour rendering index: 80

Service life [h]: 25000

Number of on/off cycles: ≥ 20000

Lighting angle [°]: 120

Luminous efficiency of the lamp [lm/W]: 72

Ambient temperature range to which the product can be exposed: 5÷25

Enclosure material: Metal

Connection type: Bolt terminal block

Range of sections of wires used [mm²]: 1,5

IP class: 20


LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 10

Number of units in the secondary packaging: 1

Number of units in the packaging: 10



37319 NIFU LED17,8W NW W/B

Ceiling-mounted LED light fitting

Net unit weight [g] : 1050
Grammage [g] : 1539.2
Gross unit weight [g] : 1428
Length of a unit pack [cm] : 45
Width of a unit pack [cm] : 9
Height of a unit pack [cm] : 45
Weight of a cardboard box [kg] : 15.392
Width of a cardboard box [cm] : 47
Height of a cardboard box [cm] : 48
Length of a cardboard box [cm] : 93
Volume of a cardboard box [m³] : 0.209808