

38385 BENO ECO 30W CCT O B

Ceiling-mounted LED light fitting

5905339383853



IP
65

HIGH
lumen

EA
SY
Installation



GENERAL DATA:

Colour: black

Place of assembly: wall mounted, ceiling mounted

Place of application: Indoors and outdoors

Minimum distance from the illuminated object: 0,5m

Compatible with a dimmer: no

Wykrywanie ruchu: no

Height [mm]: 55

Diameter [mm]: 300

Mercury content: no

Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Maximum power [W]: 30

Class of protection against electric shock: II

Lampshade material: PP

Diode type: LED SMD

Luminous flux of the light fitting [lm]: 2150 (WW) / 2400 (NW) / 2300 (CW)

Colour temperature: Warm white, white, cold white

Correlated colour temperature [K]: 3000 / 4000 / 6500

Colour consistency in McAdam ellipses: ≤6

Colour rendering index: 80

Service life [h]: 30000

Number of on/off cycles: ≥30000

Lighting angle [°]: 110

Ambient temperature range to which the product can be exposed: -20÷45

Enclosure material: PP

Connection type: Self-clamping block

Range of sections of wires used [mm²]: 0,5÷1,5

Lamp-heating time [s]: ≤1

Lamp-ignition time [s]: ≤0,5

IP class: 65

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 10


Number of units in the secondary packaging: 1

Number of units in the packaging: 10

Net unit weight [g]: 692

38385 BENO ECO 30W CCT O B

Ceiling-mounted LED light fitting



Grammage [g]: 897

Gross unit weight [g]: 844

Length of a unit pack [cm]: 30.5

Width of a unit pack [cm]: 6

Height of a unit pack [cm]: 30.5

Weight of a cardboard box [kg]: 8.97

Width of a cardboard box [cm]: 32

Height of a cardboard box [cm]: 32

Length of a cardboard box [cm]: 62

Volume of a cardboard box [m³]: 0.063488

