

38387 BENO ECO 40W CCT O B

Ceiling-mounted LED light fitting

5905339383877



IP
65

HIGH
lumen

EA
SY
Installation



GENERAL DATA:

Colour: black
Place of assembly: wall mounted, ceiling mounted
Place of application: Indoors and outdoors
Minimum distance from the illuminated object: 0,5m
Compatible with a dimmer: no
Wykrywanie ruchu: no
Height [mm]: 55
Diameter [mm]: 400
Mercury content: no
Integrated LED light source: yes

TECHNICAL DATA:


Rated voltage [V]: 220-240 AC
Rated frequency [Hz]: 50
Maximum power [W]: 40
Class of protection against electric shock: II
Lampshade material: PP
Diode type: LED SMD
Luminous flux of the light fitting [lm]: 3800 (WW) / 4050 (NW) / 3900 (CW)
Colour temperature: Warm white, white, cold white
Correlated colour temperature [K]: 3000 / 4000 / 6500
Colour consistency in McAdam ellipses: ≤6
Colour rendering index: 80
Service life [h]: 30000
Number of on/off cycles: ≥30000
Lighting angle [°]: 110
Ambient temperature range to which the product can be exposed: -20÷45
Enclosure material: PP
Connection type: Self-clamping block
Range of sections of wires used [mm²]: 0,5÷1,5
Lamp-heating time [s]: ≤1
Lamp-ignition time [s]: ≤0,5
IP class: 65

LOGISTIC DATA:

Unit of measurement: unit
Packaging method: 10
Number of units in the secondary packaging: 1
Number of units in the packaging: 10
Net unit weight [g]: 1026

38387 BENO ECO 40W CCT O B

Ceiling-mounted LED light fitting



Grammage [g]: 1339

Gross unit weight [g]: 1262

Length of a unit pack [cm]: 40.5

Width of a unit pack [cm]: 6

Height of a unit pack [cm]: 40.5

Weight of a cardboard box [kg]: 13.39

Width of a cardboard box [cm]: 42

Height of a cardboard box [cm]: 42.5

Length of a cardboard box [cm]: 62

Volume of a cardboard box [m³]: 0.11067

