

38421 FL AGOR PRO 150W NW

LED floodlight

5905339384218



GENERAL DATA:


Colour: black
Place of assembly: ceiling mounted, wall mounted
Place of application: for industrial applications
Minimum distance from the illuminated object: 1m
Compatible with a dimmer: no
Width [mm]: 291
Height [mm]: 332
Depth [mm]: 93
Mercury content: no
Mercury content in the lamp [mg]: 0
Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC
Rated frequency [Hz]: 50
Maximum power [W]: 150
Class of protection against electric shock: I
Lampshade material: Tempered glass
Diode type: LED SMD
Luminous flux [lm]: 21000
Useful luminous flux of the light source Φ_{use} [lm]: 25360
Useful luminous flux of the light source Φ_{use} [lm]: w szerokim stożku (120°)
Colour temperature: white
Correlated colour temperature [K]: 4000
Colour consistency in McAdam ellipses: 6
Colour rendering index: ≥ 80
Service life [h]: 50000
Number of on/off cycles: ≥ 25000
Lighting angle [°]: 110
Luminous efficiency of the lamp [lm/W]: 140
Ambient temperature range to which the product can be exposed: -30÷45
Enclosure material: Metal
Connection type: Free cable ends
Wire type: H05RN-F
Wire length [m]: 1
Wire diameter [mm²]: 1
The fixture is movable vertically [°]: 180
IK class: 08
IP class: 65

38421 FL AGOR PRO 150W NW

LED floodlight



LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 4

Number of units in the secondary packaging: 1

Number of units in the packaging: 4

Net unit weight [g]: 2760

Grammage [g]: 3197.5

Gross unit weight [g]: 3062

Length of a unit pack [cm]: 30.5

Width of a unit pack [cm]: 6.5

Height of a unit pack [cm]: 37.5

Weight of a cardboard box [kg]: 12.79

Width of a cardboard box [cm]: 28

Height of a cardboard box [cm]: 40

Length of a cardboard box [cm]: 32

Volume of a cardboard box [m³]: 0.03584

ADDITIONAL INFORMATION:

- 5 years Warranty under the terms of the warranty statement, available on our website