

38424 FL AGOR/A PRO 150W NW

LED floodlight

5905339384249



GENERAL DATA:

Colour: black

Place of assembly: ceiling mounted, wall mounted

Place of application: for industrial applications

Minimum distance from the illuminated object: 1m

Compatible with a dimmer: no

Width [mm]: 291

Height [mm]: 332

Depth [mm]: 93

Mercury content: no

Mercury content in the lamp [mg]: 0

Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Maximum power [W]: 150

Class of protection against electric shock: I

Lampshade material: Tempered glass

Diode type: LED SMD

Luminous flux [lm]: 20250

Useful luminous flux of the light source Φ_{use} [lm]: 24450

Useful luminous flux of the light source Φ_{use} [lm]: w szerokim stożku (120°)

Colour temperature: white

Correlated colour temperature [K]: 4000

Colour consistency in McAdam ellipses: 6

Colour rendering index: ≥ 80

Service life [h]: 50000

Number of on/off cycles: ≥ 25000

Lighting angle [°]: X125/Y65

Luminous efficiency of the lamp [lm/W]: 135

Ambient temperature range to which the product can be exposed: -30÷45

Enclosure material: Metal

Connection type: Free cable ends

Wire type: H05RN-F

Wire length [m]: 1

Wire diameter [mm²]: 1


The fixture is movable vertically [°]: 180

IK class: 08

IP class: 65

38424 FL AGOR/A PRO 150W NW

LED floodlight



LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 4

Number of units in the secondary packaging: 1

Number of units in the packaging: 4

Net unit weight [g]: 2794

Grammage [g]: 3232.5

Gross unit weight [g]: 3096

Length of a unit pack [cm]: 30.5

Width of a unit pack [cm]: 6.5

Height of a unit pack [cm]: 37.5

Weight of a cardboard box [kg]: 12.93

Width of a cardboard box [cm]: 28

Height of a cardboard box [cm]: 40

Length of a cardboard box [cm]: 32

Volume of a cardboard box [m³]: 0.03584

ADDITIONAL INFORMATION:

- 5 years Warranty under the terms of the warranty statement, available on our website